

Synthesis of Character Behavior by Dynamic Interaction of 'Synergies' Learned from MoCap data

A. Park, A. Mukovskiy, L. Omlor, M. Giese

Laboratory for Action Representation and Learning
Dept. for Cognitive Neurology
Hertie Center for Clinical Brain Research
University Tübingen

February 4th 2008



Computer Animation

Synthesizing of natural looking movements and reactive behavior in real-time is still an important problem.

1 Kinematic models driven by motion capture

(e.g. Gleicher, 1989; Bodenheimer and Rose, 1997; Arikan et al.; 2003, Safanova et al., 2004)

- + high degree of realism
- postprocessing is time consuming, much expertise is required, offline

2 Physical models for reactive behavior

(e.g. Hodgins et al., 1995; Grzeszczuk et al.; 1998; Shao et al., 2005)

- + self-organized character behavior in real-time
- often lacking rich details and simplified movements

3 Combination of the two approaches (e.g. Hsu et al.; 2005, Chai & Hodgins, 2005)

- ⇒ Possibility to synthesize a realistic animation in real-time
- ⇒ Complex dynamic systems



Computer Animation

Synthesizing of natural looking movements and reactive behavior in real-time is still an important problem.

1 Kinematic models driven by **motion capture**

(e.g. Gleicher, 1989; Bodenheimer and Rose, 1997; Arikan et al.; 2003, Safanova et al., 2004)

- + high degree of realism
- postprocessing is time consuming, much expertise is required, offline

2 Physical models for **reactive behavior**

(e.g. Hodgins et al., 1995; Grzeszczuk et al.; 1998; Shao et al., 2005)

- + self-organized character behavior in real-time
- often lacking rich details and simplified movements

3 Combination of the two approaches (e.g. Hsu et al.; 2005, Chai & Hodgins, 2005)

- ⇒ Possibility to synthesize a realistic animation in real-time
- ⇒ Complex dynamic systems



Computer Animation

Synthesizing of natural looking movements and reactive behavior in real-time is still an important problem.

1 Kinematic models driven by **motion capture**

(e.g. Gleicher, 1989; Bodenheimer and Rose, 1997; Arikan et al.; 2003, Safanova et al., 2004)

- + high degree of realism
- postprocessing is time consuming, much expertise is required, offline

2 Physical models for **reactive behavior**

(e.g. Hodgins et al., 1995; Grzeszczuk et al.; 1998; Shao et al., 2005)

- + self-organized character behavior in real-time
- often lacking rich details and simplified movements

3 Combination of the two approaches (e.g. Hsu et al.; 2005, Chai & Hodgins, 2005)

- ⇒ Possibility to synthesize a realistic animation in real-time
- ⇒ Complex dynamic systems



Computer Animation

Synthesizing of natural looking movements and reactive behavior in real-time is still an important problem.

1 Kinematic models driven by **motion capture**

(e.g. Gleicher, 1989; Bodenheimer and Rose, 1997; Arikan et al.; 2003, Safanova et al., 2004)

- + high degree of realism
- postprocessing is time consuming, much expertise is required, offline

2 Physical models for **reactive behavior**

(e.g. Hodgins et al., 1995; Grzeszczuk et al.; 1998; Shao et al., 2005)

- + self-organized character behavior in real-time
- often lacking rich details and simplified movements

3 Combination of the two approaches (e.g. Hsu et al.; 2005, Chai & Hodgins, 2005)


- ⇒ Possibility to synthesize a realistic animation in real-time
- ⇒ Complex dynamic systems



The Idea of Synergies

Motor Control

- Classical idea in motor control: Decomposition in low-dimensional control units with few DOF \Rightarrow **Synergies** (e.g. Bernstein, 1967; Flash & Hochner, 2005)
- Extraction of movement primitives from EMG data using unsupervised learning methods like PCA, ICA (e.g. d'Avella et al., 2003; Ivanenko et al., 2005)



\Rightarrow Few movement primitives sufficient to generate different movements


The concept of movement primitives can be transferred to computer animation!



The Idea of Synergies

Motor Control

- Classical idea in motor control: Decomposition in low-dimensional control units with few DOF \Rightarrow **Synergies** (e.g. Bernstein, 1967; Flash & Hochner, 2005)
- Extraction of movement primitives from EMG data using unsupervised learning methods like PCA, ICA (e.g. d'Avella et al., 2003; Ivanenko et al., 2005)



\Rightarrow Few movement primitives sufficient to generate different movements


The concept of movement primitives can be transferred to computer animation!



The Idea of Synergies

Motor Control

- Classical idea in motor control: Decomposition in low-dimensional control units with few DOF \Rightarrow **Synergies** (e.g. Bernstein, 1967; Flash & Hochner, 2005)
- Extraction of movement primitives from EMG data using unsupervised learning methods like PCA, ICA (e.g. d'Avella et al., 2003; Ivanenko et al., 2005)



\Rightarrow Few movement primitives sufficient to generate different movements


The concept of movement primitives can be transferred to computer animation!



The Idea of Synergies

Motor Control

- Classical idea in motor control: Decomposition in low-dimensional control units with few DOF \Rightarrow **Synergies** (e.g. Bernstein, 1967; Flash & Hochner, 2005)
- Extraction of movement primitives from EMG data using unsupervised learning methods like PCA, ICA (e.g. d'Avella et al., 2003; Ivanenko et al., 2005)



\Rightarrow Few movement primitives sufficient to generate different movements

The concept of movement primitives can be transferred to computer animation!




Main Goals

- Learning of movement primitives from full-body MoCap data
- Transformation of such trajectory models into a real-time capable animation system
- High-quality animation of complex human movements
- Interactive behavior and crowd animation



Learning of Movement Primitives

- **Motion Capturing** of natural, emotional straight and cyclic walking
- **Extraction of primitives** by using ICA on full-body joint angles
 ⇒ Source signals very similar, but time-shifted against each other
- **Generative mixing model:** Superposition of independent shift-invariant source signals



Joint angle trajectories

$$x_i(t) = \sum_j w_{ij} s_j(t - \tau_{ij})$$


unknown sources
unknown weights
unknown phase shifts

Unknowns: mixing weights w_{ij} , source signals s_j , delays τ_{ij}



Learning of Movement Primitives

- **Motion Capturing** of natural, emotional straight and cyclic walking
- **Extraction of primitives** by using ICA on full-body joint angles
 ⇒ Source signals very similar, but time-shifted against each other
- **Generative mixing model:** Superposition of independent shift-invariant source signals



$$x_i(t) = \sum_j w_{ij} s_j(t - \tau_{ij})$$

Joint angle trajectories

unknown sources

unknown weights


unknown phase shifts

Unknowns: mixing weights w_{ij} , source signals s_j , delays τ_{ij}



Learning of Movement Primitives

- **Motion Capturing** of natural, emotional straight and cyclic walking
- **Extraction of primitives** by using ICA on full-body joint angles
 ⇒ Source signals very similar, but time-shifted against each other
- **Generative mixing model:** Superposition of independent shift-invariant source signals



$$x_i(t) = \sum_j w_{ij} s_j(t - \tau_{ij})$$

Joint angle trajectories

unknown sources

unknown weights

unknown phase shifts

Unknowns: mixing weights w_{ij} , source signals s_j , delays τ_{ij}



New Blind Source Separation Algorithm

New algorithm based on **Wigner-Ville transformation**. (Omlor & Giese, NIPS 2006)

Mixing model to solve:

$$x_i(t) = \sum_j w_{ij} s_j(t - \tau_{ij})$$

time frequency

$$Wx_i(\eta, \omega) = \sum_j w_{ij}^2 Ws_j(\eta - \tau_{ij}, \omega)$$

Wigner transformation

Projection onto lower dim. spaces

$$\int \dots d\eta, \int \dots \eta d\eta$$

$$(1) \quad |\tilde{x}_i(\omega)|^2 = \sum_j |w_{ij}|^2 |\tilde{s}_j(\omega)|^2$$

Amplitudes of sources and weights estimated by **positive ICA**.

$$(2) \quad |\tilde{x}_i(\omega)|^2 \frac{\partial}{\partial \omega} \arg\{\tilde{x}_i(\omega)\} =$$

$$\sum_n |w_{ij}|^2 |\tilde{s}_j(\omega)|^2 \left[\frac{\partial}{\partial \omega} \arg\{\tilde{s}_j(\omega)\} + \tau_{ij} \right]$$

Phases of source signals and delays recovered



Sources, linear weights and the phase shifts



Approximation Quality

original

new algorithm 3 sources

PCA 6 sources



Real-Time System

- Source signals are periodic
 \Rightarrow desired behavior must be driven by a stable solution of a nonlinear dynamical system:


Van der Pol Oscillator

$$\ddot{y}(t) + \underbrace{\lambda(y(t)^2 - k)}_{\text{Amplitude-dependent damping term}} \dot{y}(t) + \omega_0^2 y(t)$$

Amplitude-dependent damping term

- Mapping is realized by nonlinear Support Vector Regression

$$s_j(t - \tau_{ij}) = \tilde{s}_{ij}(t) = f_{ij}(y_j(t), \dot{y}_j(t))$$



Real-Time System

- Source signals are periodic
 \Rightarrow desired behavior must be driven by a stable solution of a nonlinear dynamical system:

Van der Pol Oscillator


$$\ddot{y}(t) + \underbrace{\lambda(y(t)^2 - k)}_{\text{Amplitude-dependent damping term}} \dot{y}(t) + \omega_0^2 y(t)$$

Amplitude-dependent damping term

- Mapping is realized by nonlinear Support Vector Regression

$$s_j(t - \tau_{ij}) = \tilde{s}_{ij}(t) = f_{ij}(y_j(t), \dot{y}_j(t))$$

\Rightarrow Generating trajectories by application of the mixing model




Stabilization by Dynamic Coupling

- Dynamic coupling between oscillators to stabilize coordination
- Form of coupling derived from Lohmiller & Slotine (2000) permits design of oscillator networks with a single stable solution
 ⇒ Velocity coupling:

$$\ddot{y}_1 + \lambda (y_1^2 - k) \dot{y}_1 + \omega_0^2 y_1 = \alpha (\dot{y}_2 - \dot{y}_1) + \alpha (\dot{y}_3 - \dot{y}_1)$$

$$\ddot{y}_2 + \lambda (y_2^2 - k) \dot{y}_2 + \omega_0^2 y_2 = \alpha (\dot{y}_1 - \dot{y}_2) + \alpha (\dot{y}_3 - \dot{y}_2)$$

$$\ddot{y}_3 + \lambda (y_3^2 - k) \dot{y}_3 + \omega_0^2 y_3 = \alpha (\dot{y}_1 - \dot{y}_3) + \alpha (\dot{y}_2 - \dot{y}_3)$$



⇒ Complex systems build from contracting elements are contracting



Stabilization by Dynamic Coupling


- Dynamic coupling between oscillators to stabilize coordination
- Form of coupling derived from Lohmiller & Slotine (2000) permits design of oscillator networks with a single stable solution

⇒ Velocity coupling:

$$\ddot{y}_1 + \lambda (y_1^2 - k) \dot{y}_1 + \omega_0^2 y_1 = \alpha (\dot{y}_2 - \dot{y}_1) + \alpha (\dot{y}_3 - \dot{y}_1)$$

$$\ddot{y}_2 + \lambda (y_2^2 - k) \dot{y}_2 + \omega_0^2 y_2 = \alpha (\dot{y}_1 - \dot{y}_2) + \alpha (\dot{y}_3 - \dot{y}_2)$$

$$\ddot{y}_3 + \lambda (y_3^2 - k) \dot{y}_3 + \omega_0^2 y_3 = \alpha (\dot{y}_1 - \dot{y}_3) + \alpha (\dot{y}_2 - \dot{y}_3)$$




⇒ Complex systems build from contracting elements are contracting



Coordinated Behavior of Crowds

- Dynamic coupling of multiple avatars




- Self-organized synchronized behavior
- Translation and rotation is computed from foot-ground contact events



Coordinated Behavior of Crowds

- Dynamic coupling of multiple avatars




- Self-organized synchronized behavior
- Translation and rotation is computed from foot-ground contact events



Coordinated Behavior of Crowds

- Dynamic coupling of multiple avatars
- Self-organized synchronized behavior
- Translation and rotation is computed from foot-ground contact events




Interactive Behavior

Modulation of walking speed by change of the eigenfrequency ω_0 dependent on the distance $d(t)$ between characters

$$\omega_0(t) = f(d(t))$$

Example: **Following** behavior



Style Morphing

- Same sources and delays for all styles
 - Styles (curved and emotional gaits) are defined by weight matrix
- ⇒ Style changes by blending weights using linear interpolation:

$$w_{ij}(t) = \mu(t) w_{ij}^a + (1 - \mu(t)) w_{ij}^b$$

- Navigation as an example of style morphing:
morphing weights μ depend on the change of heading direction φ_i

$$\mu(t) \sim \frac{d\varphi_i}{dt}$$



Style Morphing

- Same sources and delays for all styles
 - Styles (curved and emotional gaits) are defined by weight matrix
- ⇒ Style changes by blending weights using linear interpolation:

$$w_{ij}(t) = \mu(t) w_{ij}^a + (1 - \mu(t)) w_{ij}^b$$

- Navigation as an example of style morphing:
morphing weights μ depend on the change of heading direction φ_i

$$\mu(t) \sim \frac{d\varphi_i}{dt}$$



Navigation Dynamics

For interactive behavior a navigation model is required

- Navigation dynamics from robotics (Schöner & Dose, 1995; Warren, 2006)
- The change of the heading direction is determined by the sum of three terms where \mathbf{p}_i denotes the position of the character i :

$$d\varphi_i/dt = \underbrace{h^{\text{goal}}(\varphi_i, \mathbf{p}_i, \mathbf{p}_i^{\text{goal}})}_{\text{goal-finding term}} + \underbrace{\sum_j h^{\text{avoid}}(\varphi_i, \mathbf{p}_i, \mathbf{p}_j)}_{\text{instantaneous obstacle avoidance}} + \underbrace{\sum_j h^{\text{pcoll}}(\varphi_i, \varphi_j, \mathbf{p}_i, \mathbf{p}_j)}_{\text{predictive obstacle avoidance}}$$



Navigation Dynamics

For interactive behavior a navigation model is required

- Navigation dynamics from robotics (Schöner & Dose, 1995; Warren, 2006)
- The change of the heading direction is determined by the sum of three terms where \mathbf{p}_i denotes the position of the character i :

$$d\varphi_i/dt = \underbrace{h^{\text{goal}}(\varphi_i, \mathbf{p}_i, \mathbf{p}_i^{\text{goal}})}_{\text{goal-finding term}} + \underbrace{\sum_j h^{\text{avoid}}(\varphi_i, \mathbf{p}_i, \mathbf{p}_j)}_{\text{instantaneous obstacle avoidance}} + \underbrace{\sum_j h^{\text{pcoll}}(\varphi_i, \varphi_j, \mathbf{p}_i, \mathbf{p}_j)}_{\text{predictive obstacle avoidance}}$$



Navigation Dynamics

For interactive behavior a navigation model is required

- Navigation dynamics from robotics (Schöner & Dose, 1995; Warren, 2006)
- The change of the heading direction is determined by the sum of three terms where \mathbf{p}_i denotes the position of the character i :

$$d\varphi_i/dt = \underbrace{h^{\text{goal}}(\varphi_i, \mathbf{p}_i, \mathbf{p}_i^{\text{goal}})}_{\text{goal-finding term}} + \underbrace{\sum_j h^{\text{avoid}}(\varphi_i, \mathbf{p}_i, \mathbf{p}_j)}_{\text{instantaneous obstacle avoidance}} + \underbrace{\sum_j h^{\text{pcoll}}(\varphi_i, \varphi_j, \mathbf{p}_i, \mathbf{p}_j)}_{\text{predictive obstacle avoidance}}$$



Control of Walking Direction

- 1 **Goal-finding term:** (where φ_i^{goal} is goal direction angle of character i)



$$h^{\text{goal}}(\varphi_i, \mathbf{p}_i, \mathbf{p}_i^{\text{goal}}) = \sin(\varphi_i^{\text{goal}} - \varphi_i)$$

- 2 **Instantaneous obstacle avoidance:**

$$h^{\text{avoid}}(\varphi_i, \mathbf{p}_i, \mathbf{p}_j) = \sin(\varphi_i - \varphi_{ij}) \cdot \exp\left(-\frac{(\varphi_{ij} - \varphi_i)^2}{2\sigma_\varphi^2}\right) \cdot \exp\left(-\frac{d_{ij}^2}{2\sigma_d^2}\right)$$

- 3 **Predictive obstacle avoidance:**

$$h^{\text{pcoll}}(\varphi_i, \varphi_j, \mathbf{p}_i, \mathbf{p}_j) = \sin(\varphi_i - \varphi_{ij}^{\text{pc}}) \cdot \exp\left(-\frac{(\varphi_{ij}^{\text{pc}} - \varphi_i)^2}{2\sigma_\varphi^2}\right) \cdot \exp\left(-\frac{(d_{ij}^{\text{pc}})^2}{2\sigma_d^2}\right)$$



Control of Walking Direction

- 1 **Goal-finding term:** (where φ_i^{goal} is goal direction angle of character i)



$$h^{\text{goal}}(\varphi_i, \mathbf{p}_i, \mathbf{p}_i^{\text{goal}}) = \sin(\varphi_i^{\text{goal}} - \varphi_i)$$

- 2 **Instantaneous obstacle avoidance:**

$$h^{\text{avoid}}(\varphi_i, \mathbf{p}_i, \mathbf{p}_j) = \sin(\varphi_i - \varphi_{ij}) \cdot \exp\left(-\frac{(\varphi_{ij} - \varphi_i)^2}{2\sigma_\varphi^2}\right) \cdot \exp\left(-\frac{d_{ij}^2}{2\sigma_d^2}\right)$$

- 3 **Predictive obstacle avoidance:**

$$h^{\text{pcoll}}(\varphi_i, \varphi_j, \mathbf{p}_i, \mathbf{p}_j) = \sin(\varphi_i - \varphi_{ij}^{\text{pc}}) \cdot \exp\left(-\frac{(\varphi_{ij}^{\text{pc}} - \varphi_i)^2}{2\sigma_\varphi^2}\right) \cdot \exp\left(-\frac{(d_{ij}^{\text{pc}})^2}{2\sigma_d^2}\right)$$



Control of Walking Direction

- 1 **Goal-finding term:** (where φ_i^{goal} is goal direction angle of character i)



$$h^{\text{goal}}(\varphi_i, \mathbf{p}_i, \mathbf{p}_i^{\text{goal}}) = \sin(\varphi_i^{\text{goal}} - \varphi_i)$$

- 2 **Instantaneous obstacle avoidance:**

$$h^{\text{avoid}}(\varphi_i, \mathbf{p}_i, \mathbf{p}_j) = \sin(\varphi_i - \varphi_{ij}) \cdot \exp\left(-\frac{(\varphi_{ij} - \varphi_i)^2}{2\sigma_\varphi^2}\right) \cdot \exp\left(-\frac{d_{ij}^2}{2\sigma_d^2}\right)$$


- 3 **Predictive obstacle avoidance:**

$$h^{\text{pcoll}}(\varphi_i, \varphi_j, \mathbf{p}_i, \mathbf{p}_j) = \sin(\varphi_i - \varphi_{ij}^{\text{pc}}) \cdot \exp\left(-\frac{(\varphi_{ij}^{\text{pc}} - \varphi_i)^2}{2\sigma_\varphi^2}\right) \cdot \exp\left(-\frac{(d_{ij}^{\text{pc}})^2}{2\sigma_d^2}\right)$$




Navigation Demos


Navigation with emotional changes (from neutral to sad)



Navigation with emotional changes (from sad to happy)



Self-Organized Dancing Scenario of a 'Welsh Folk Dance'



Related work for synchron. dance perform. with music: (e.g. Takaaki Shiratori et al., 2006; Shinichiro Nakaoka et al., 2004)



Conclusion

- Simulation of realistic human movements based on learned components of MoCap trajectories, inspired by the concept of 'synergies'
- New more compact method of learning spatial components based on ICA with time-delays
- Real-time capable system: Mapping nonlinear dynamical systems onto the source signals using SVR
- Generating coordinated behavior by coupling dynamic primitives
- Navigation as an example for interactive behavior



Conclusion

- Simulation of realistic human movements based on learned components of MoCap trajectories, inspired by the concept of 'synergies'
- New more compact method of learning spatial components based on ICA with time-delays
- Real-time capable system: Mapping nonlinear dynamical systems onto the source signals using SVR
- Generating coordinated behavior by coupling dynamic primitives
- Navigation as an example for interactive behavior



Conclusion

- Simulation of realistic human movements based on learned components of MoCap trajectories, inspired by the concept of 'synergies'
- New more compact method of learning spatial components based on ICA with time-delays
- Real-time capable system: Mapping nonlinear dynamical systems onto the source signals using SVR
- Generating coordinated behavior by coupling dynamic primitives
- Navigation as an example for interactive behavior



Conclusion

- Simulation of realistic human movements based on learned components of MoCap trajectories, inspired by the concept of 'synergies'
- New more compact method of learning spatial components based on ICA with time-delays
- Real-time capable system: Mapping nonlinear dynamical systems onto the source signals using SVR
- Generating coordinated behavior by coupling dynamic primitives
- Navigation as an example for interactive behavior



Conclusion

- Simulation of realistic human movements based on learned components of MoCap trajectories, inspired by the concept of 'synergies'
- New more compact method of learning spatial components based on ICA with time-delays
- Real-time capable system: Mapping nonlinear dynamical systems onto the source signals using SVR
- Generating coordinated behavior by coupling dynamic primitives
- Navigation as an example for interactive behavior



Future Work

- Extension for non-periodic primitives and more complex movements
- Application to facial movements



Future Work

- Extension for non-periodic primitives and more complex movements
- Application to facial movements



Thanks to

- Claire Roether
Winfried Ilg
- Special thanks to:
Jean-Jacques Slotine (MIT)
Wolfgang Strasser (Uni-Tüb.)
- funded by DFG (Perceptual Graphics)

